



C140-160-200/32

FLATWORK DRYING IRONERS FRONT RETURN

Flatwork dryer-ironers

C140-160-200/32

Front-service type to be used by one or two operators, with possibility of approaching the rotary drying press to the wall. Perfect ironing and drying thanks to NOMEX® belts winding on nearly the whole roller surface. Easy loading of laundry thanks to the laundry conveying strips allowing easy handling of the appliance. Effective width 140 ÷ 160 ÷ 200cm. Digital thermostat to select different temperatures and constant visual control of the attained temperature. Safety thermostat to avoid undesirable overheating. Adjustable roller revolving speed from 0.1m/min till 9m/min through frequency controlled motor. Finger-saving fillet to protect the operator in case of wrong operation. Manual device to move the roller and to take off the laundry in case of power failure. Electronic device to start and to control the gas flame; Chrome plated cylinder on request;



Warning

Do not use gas drying-ironers in rooms where perchlore is used as well.

Electronic control ST23

ST23 control, standard on the entire gamma, manages temperature using the P.I.D. system (Proportional - Integral - Derivative).



Models C/32

		140	160	200
Usable length	mm	1400	1600	200
Cylinder dimensions	Diameter (mm)	325	325	325
	Heated surface (m²)	1.42	1.63	2.04
	Speed (mt/min)	1 ÷ 6.5	1 ÷ 6.5	1 ÷ 6.5
Exhaust	Number	1	1	2
	Diameter (mm)	98	98	2 x 98
	Extraction power (m³/h)	500	500	2 x 500
Capacity	kg/h	10 ÷ 20	20 ÷ 30	30 ÷ 40
	Water evaporation (l/h)	7 ÷ 14	14 ÷ 21	21 ÷ 28
Noise	dB	60	60	63

Net dimensions and packing

Net dimensions	Width (mm)	1960	2210	2560
	Depth (mm)	644	644	644
	Height (mm)	1107	1107	1107
Packing dimensions	Width (mm)	2340	2340	2740
	Depth (mm)	770	770	770
	Eight (mm)	1400	1400	1400
	Volume (m3)	2.52	2.52	2.95
Net / gross weight	kg	335 ÷ 355	375 ÷ 395	335 ÷ 355

Electric heated models

Power supply	V / ph / Hz	230-240V 3~50/60Hz	230-240V 3~50/60Hz	230-240V 3~50/60Hz
		380-415V 3~N 50/60Hz	380-415V 3~N 50/60Hz	380-415V 3~N 50/60Hz
		440-480V 3~ 60Hz	440-480V 3~ 60Hz	440-480V 3~ 60Hz
Electric thermal power	kW	12	16	21
Motor power	kW	0.37	0.37	0.49
Total power	kW	12.37	16.37	21.49
Fuse	A	20 ÷ 32	25 ÷ 50	32 ÷ 63

Gas heated models

Power supply	V / ph / Hz	230-240V 3~50/60Hz	230-240V 3~50/60Hz	230-240V 3~50/60Hz
		380-415V 3~N 50/60Hz	380-415V 3~N 50/60Hz	380-415V 3~N 50/60Hz
		440-480V 3~ 60Hz	440-480V 3~ 60Hz	440-480V 3~ 60Hz
Gas thermal power	kW	14	22.5	30
Natural gas consumption	m³/h	1.5	2.4	3.2
Liquid gas consumption	kg/h	1.1	1.7	2.3
Motor power	kW	0.37	0.37	0.49
Total electric power	kW	4	7.5	7.5
Fuse	A	2 ÷ 2	2 ÷ 2	2 ÷ 2

C140-160-200/32 201607 rel.02 REF GR000000000006

The manufacturer declines all responsibility for any inexactitudes contained in this catalogue. The manufacturer reserves the right to bring, without warning, any modifications he might believe necessary, without changing the essential characteristics of the product.

grandimpianti i.l.e - Ali spa
via masiere, 211/c - 32037 sospiolo (BL) Italy
ph. +39 0437 848 711 - fax +39 0437 879 108
www.grandimpianti.com - info@grandimpianti.com



COMPANY WITH
MANAGEMENT SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =
= ISO 14001 =

an Ali Group Company



The Spirit of Excellence